

zencontrol

Plug-in Smart exit **datasheet**



Features

- Slimblade recessed exit with 300 x 150 mm decal
- Plug-in expansion for Emergency Smart driver range
- High Quality Lithium battery (LiFePO₄) and smart charger
- Wall / surface / pendant or recessed mount options
- Single DALI address for LED driver and emergency
- Single and double sided decals



Device type 1

Functions as a maintained IEC62386-202 device



Low power consumption

Adds less than a 50 mW to the standby power



Plug-in upgrade

Simply plug-in battery and test switch to upgrade device



Single point unit

Out of the box the OEM works as a SPU

zencontrol

Plug-in Smart exit datasheet



Product range

Order code	Description
zc-smart-exit-150	300x150 mm, Emergency exit expansion kit for zc-smart-driver-em*

Features

- Slimblade recessed exit with 300 x 150 mm decal
- Plug-in expansion for Emergency Smart driver range*
- High Quality Lithium battery (LiFePO₄) and smart charger
- Wall / surface / pendant or recessed mount options
- Single DALI address for LED driver and emergency
- Less than 0.75 W average power consumption
- Compliant emergency exit sign

Kit content

300x150 mm, Emergency exit expansion kit for zc-smart-driver-em*

1500 mAh, 2 cell, LiFePO₄ battery with holder

Surface mount kit

Wall mount kit

RJ12 connection cable, 1.9 m

Supported models*

Order code	Description
zc-smart-driver-em-40	40 W DALI Smart driver with emergency, softwire plug
zc-smart-driver-em-40-t	40 W DALI Smart driver with emergency, screw-terminal
zc-smart-driver-em-40-p	40 W DALI Smart driver with emergency, push-terminal
zc-smart-driver-em-40-au	40 W DALI Smart driver with emergency, 90 min, softwire plug
zc-smart-driver-em-40-au-t	40 W DALI Smart driver with emergency, 90 min, screw-terminal

Accessory range

Order code	Description
zc-exit-rm-kit	Recessed mount kit
zc-exit-150-decal-kit	300 x 150 mm decal kit

Specifications

Supply voltage	Powered from zc-smart-driver-em*	
Classification	3	
Wiring	Plug-in loom	
Material	PC (body)	
Mounting	Surface mounted (wall and ceiling), (pendant accessory sold separately)	
Cut-out	Max. 60 mm for Surface mount kit	
Decal size	300 x 150 mm	
Viewing distance	EU 30M AU/NZ 24M	
Operating temperature	0 to 40°C	
Ingress protection	IP20	
Emergency	Rated duration	3 hours
	Testing	Standalone Self test (per IEC62034) DALI Self test (per IEC62386-202)
Battery**	Code	zc-batt-1500mah
	Type	LiFePO ₄
	Voltage	6.4 V
Charger**	Type	Smart charge
	Time	16 hours
	Operation	Multi-state
Compliance standards	IEC 60598-2-22 CISPR 15 IEC 62034 IEC 62386-202	

** Per driver specifications

Dimensions (mm)

